

TEST REPORT

Applicant: Skydroid Technology (Fujian) Co., Ltd.

Address of Applicant: Building E, No. 249, Keji Road, Fengze District, Quanzhou City, Fujian, China

Manufacturer/Factory: Skydroid Technology (Fujian) Co., Ltd.

Address of Manufacturer/Factory: Building E, No. 249, Keji Road, Fengze District, Quanzhou City, Fujian, China

Factory: Skydroid Technology (Fujian) Co., Ltd.

Address of Factory: Building E, No. 249, Keji Road, Fengze District, Quanzhou City, Fujian, China

Equipment Under Test (EUT)

Product Name: Remote control

Model No.: G12-H,G12-H Pro,G12-H/G12-H Pro,GR01

Trade Mark: SKYDROID

Applicable standards: ETSI EN 300 440 V2.1.1 (2017-03)

Date of sample receipt: July 13, 2026

Date of Test: July 13, 2026~ Aug 15, 2026

Date of report issue: Aug 25, 2026

Test Result : PASS *

*In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:


Robinson Luo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	Aug 25, 2026	Original

Tested By:




Date:

Aug 25, 2026

Test Engineer

Prepared By:




Date:

Aug 25, 2026

Project Engineer

Check By:



Date:

Aug 25, 2026

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 TEST FACILITY	7
5.4 TEST LOCATION	7
5.5 DESCRIPTION OF SUPPORT UNITS	7
5.6 DEVIATION FROM STANDARDS	7
5.7 ABNORMALITIES FROM STANDARD CONDITIONS.....	7
5.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	7
5.9 MEASUREMENT UNCERTAINTY	8
6 TEST INSTRUMENTS LIST	9
7 RADIO TECHNICAL REQUIREMENTS SPECIFICATION IN EN 300 440.....	11
7.1 TEST ENVIRONMENT	11
7.2 SPECTRUM ACCESS TECHNIQUES	12
7.3 TRANSMITTER REQUIREMENT	12
7.3.1 Equivalent Isotropically Radiated Power	12
7.3.2 Frequency Range	13
7.3.3 Duty Cycle.....	15
7.3.4 Transmitter Spurious emissions	15
7.3.5 Additional Requirement for FHSS Equipment	17
7.3.6 Hopping Channel Number.....	17
7.3.7 Dwell time	17
7.4 RECEIVER REQUIREMENTS.....	18
7.4.1 Receiver Classification.....	18
7.4.2 Adjacent Channel Selectivity.....	19
7.4.3 Blocking or desensitization	20
7.4.4 Spurious emissions.....	21
8 TEST SETUP PHOTO	23
9 EUT CONSTRUCTIONAL DETAILS	23

4 Test Summary

Radio Spectrum Matter (RSM) Part of Transmitter					
Test item	Test Requirement	Test method	Limit/Severity	Uncertainty	Result
Equivalent isotropically radiated power	EN 300 440 Clause 4.2.2	EN 300 440 Clause 4.2.2.3	Clause 4.2.2.4 Table 2	$\pm 3\text{dB}$	Pass
Permitted Range of Operating Frequencies	EN 300 440 Clause 4.2.3	EN 300 440 Clause 4.2.3.3	Clause 4.2.3.5 & Table 2	$\pm 10^{-7}$	Pass
Duty cycle	EN 300 440 Clause 4.2.5	EN 300 440 Clause 4.2.5.3	Clause 4.2.5.4 Table 4	N/A	N/A
Transmitter spurious emissions	EN 300 440 Clause 4.2.4	EN 300 440 Clause 4.2.4.3	Clause 4.2.4.4 Table 3	$\pm 6\text{ dB}$	Pass
Hopping Channel Number	EN 300 440 Clause 4.2.6	EN 300 440 Clause 4.2.6.3	≥ 20	N/A	N/A
Dwell time	EN 300 440 Clause 4.2.6	EN 300 440 Clause 4.2.6.3	Not exceed 1s	N/A	N/A
Radio Spectrum Matter (RSM) Part of Receiver					
Receiver spurious emissions	EN 300 440 Clause 4.3.5	EN 300 440 Clause 4.3.5.3	$<2\text{nW } <1\text{GHz},$ $<20\text{nW } >1\text{GHz}$	$\pm 6\text{dB}$	Pass
Adjacent channel selectivity	EN 300 440 Clause 4.3.3	Clause 4.3.3.3	Clause 4.3.3.4 Table 6	$\pm 2.5\text{dB}$	N/A
Blocking or desensitization	EN 300 440 Clause 4.3.4	EN 300 440 Clause 4.3.4.3	Clause 4.3.4.4 Table 7	$\pm 2.5\text{dB}$	Pass
Technical requirements specifications					
Spectrum access techniques	EN 300 440 Clause 4.4	PASS (Declared by manufacture)			

Remarks:

Pass: The EUT complies with the essential requirements in the standard.

N/A: Not applicable.

5 General Information

5.1 General Description of EUT

Product Name:	Remote control
Model No.:	G12-H, G12-H Pro,G12-H/G12-H Pro,GR01
Operation Frequency:	5750MHz ~ 5820MHz
Channel separation:	10MHz, 20MHz
Modulation technology:	Orthogonal Frequency Division Multiplexing(OFDM)
Antenna Type:	Dipole Antenna
Antenna gain:	2.73dBi(Declared by applicant)
Power supply:	Battery Model: 1160100 Nominal Voltage: 3.7V Capacity: 10000mAh, 37Wh Adapter Model: GS-45W0348 Input: 100-240V~50/60Hz, 1.2A Output: 5V=3A 15.0W, 9V=3A 27.0W,12V=3A 36W, 15V=3A 45W 20V=2.25A 45W(PPS), 5V-20V=2.25A (11.25W-45.0W)
Remark:	All the models are electrical identical including the same software parameter and hardware design, Only the model name is different. Main test model is G12-H.

Disclaimer statement:

1. Antenna gain information provided by the customer, and the laboratory is not responsible for its authenticity.
2. The information in this section is provided by the applicant or manufacturer, GTS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

Frequency List:

Channel List for SRD (10MHz&20MHz bandwidth) @ 5.8G band							
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	5750	2	5760	3	5770	4	5780
5	5790	6	5800	7	5810	8	5820

5.2 Test mode

Transmitting mode	Keep the EUT in transmitting mode with modulation.
Receiving mode	Keep the EUT in receiving mode with modulation.

5.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: ● FCC—Registration No.: 381383 Designation Number: CN5029 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. ● ISED —Registration No.: 9079A CAB identifier: CN0091 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing ● NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.4 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.5 Description of Support Units

None.

5.6 Deviation from Standards

None.

5.7 Abnormalities from Standard Conditions

None.

5.8 Other Information Requested by the Customer

None.

5.9 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 3\text{dB}$
6	Conducted Spurious emissions	$\pm 2.58\text{dB}$
7	AC Power Line Conducted Emission	$\pm 3.44\text{dB}$ (0.15MHz ~ 30MHz)
8	Radiated Spurious emission test	$\pm 3.1\text{dB}$ (9kHz-30MHz)
		$\pm 3.8039\text{dB}$ (30MHz-200MHz)
		$\pm 3.9679\text{dB}$ (200MHz-1GHz)
		$\pm 4.29\text{dB}$ (1GHz-18GHz)
		$\pm 3.30\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Time	$\pm 3\%$

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Apr. 10, 2026	Apr. 09, 2027
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 10, 2026	Apr. 09, 2027
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Apr. 11, 2026	Apr. 10, 2027
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 11, 2026	Apr. 10, 2027
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Jul 10, 2026	Jul 09, 2027
7	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov.22, 2025	Nov.21, 2026
8	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 10, 2026	Apr. 09, 2027
9	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 10, 2026	Apr. 09, 2027
10	Horn Antenna (18GH-40GHz)	Schwarzbeck	BBHA 9170	GTS691	Apr. 11, 2026	Apr. 10, 2027
11	FSV-Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	Mar. 10, 2026	Mar. 09, 2027
12	Amplifier	/	LNA-1000-30S	GTS650	Apr. 10, 2026	Apr. 09, 2027
13	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 24, 2025	Nov. 23, 2026
14	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 10, 2026	Apr. 09, 2027
15	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 13, 2026	Apr. 12, 2027
16	RE cable 1	GTS	N/A	GTS675	Jul 10, 2026	Jul 09, 2027
17	RE cable 2	GTS	N/A	GTS676	Jul 10, 2026	Jul 09, 2027
18	RE cable 3	GTS	N/A	GTS677	Jul 10, 2026	Jul 09, 2027
19	RE cable 4	GTS	N/A	GTS678	Jul 10, 2026	Jul 09, 2027
20	RE cable 5	GTS	N/A	GTS679	Jul 10, 2026	Jul 09, 2027
21	RE cable 6	GTS	N/A	GTS680	Jul 10, 2026	Jul 09, 2027
22	RE cable 7	GTS	N/A	GTS681	Jul 10, 2026	Jul 09, 2027
23	RE cable 8	GTS	N/A	GTS682	Jul 10, 2026	Jul 09, 2027
24	EMI Test Software	AUDIX	E3-6.100614a	GTS725	N/A	N/A

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	Apr. 10, 2026	Apr. 09, 2027
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Jun. 03, 2026	Jun. 02, 2027
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	Apr. 10, 2026	Apr. 09, 2027
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	Apr. 10, 2026	Apr. 09, 2027
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	Apr. 10, 2026	Apr. 09, 2027
6	Wideband Power Meter	Keysight	N1924A	GTS673	Apr. 10, 2026	Apr. 09, 2027
7	USB RF Power Sensor	DARE	RPR3006W	GTS569	Apr. 10, 2026	Apr. 09, 2027
8	RF Switch Box	Shongyi	RFSW3003328	GTS571	Apr. 10, 2026	Apr. 09, 2027
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	Apr. 10, 2026	Apr. 09, 2027
10	Thermo meter	JINCHUANG	GSP-8A	GTS641	Apr. 14, 2026	Apr. 13, 2027
11	EXA Signal Analyzer	Keysight	N9010B	MY60241168	Nov. 01, 2025	Oct. 31, 2026

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	Jul. 15, 2026	Jul. 14, 2027

7 Radio Technical Requirements Specification in EN 300 440

7.1 Test environment

Test Condition	Temperature	Relative Humidity	Voltage		
			AC mains	Lead-acid battery on vehicles	Other power sources
Normal	+15°C to +35°C	20% to 75%	nominal	1,1 times the nominal voltage	nominal
Extreme	-20°C to +55°C (General use) -20°C to +55°C (Portable use) 5°C to +35°C (Indoor use)	20% to 75%	▼ 0,9 times ▲ 1,1 times	▼ 0,9 times ▲ 1,3 times	▼ 0,85 times (Leclanché or lithium) 0,9 times (mercury or nickel-cadmium) ▲ 1,15 times

Operating Environment:			
Item	Normal condition	Extreme condition	
		HT	LT
Temperature	+15°C to + 35°C	+55°C	-10°C
Voltage		DC 3.7V	
Humidity		20%-95%	
Atmospheric Pressure:		1008 mbar	

7.2 Spectrum access techniques

PASS, The EUT conform to the requirements of the clause. (Declared by manufacture)

7.3 Transmitter requirement

7.3.1 Equivalent Isotropically Radiated Power

Test Requirement:	ETSI EN 300 440 clause 4.2.2
Test Method:	ETSI EN 300 440 clause 4.2.2.3
Limit:	13.98dBm
Test procedure:	Radiated measurements shall be performed in an anechoic chamber. 1. The transmitter under test shall be placed on the support in its standard position and switched on. 2. The test antenna shall be oriented initially for vertical polarization. The test antenna shall be raised or lowered, through the specified height range until the maximum signal level is detected on the measuring receiver. 3. The transmitter shall be rotated through 360° about a vertical axis to maximize the received signal. 4. The test antenna shall be raised or lowered again, if necessary, through the specified height range until a maximum is obtained. This level shall be recorded. 5. This measurement shall be repeated for horizontal polarization. 6. The substitution antenna, shall replace the transmitter antenna in the same position and in vertical polarization. The frequency of the signal generator shall be adjusted to the transmitter (carrier) frequency. 7. Steps 2> to 5> shall be repeated. 8. The input signal to the substitution antenna shall be adjusted in level until an equal or a known related level to that detected from the transmitter is obtained in the test receiver. 9. This measurement shall be repeated with horizontal polarization. 10. The radiated power is equal to the power supplied by the signal generator, increased by the known relationship if necessary and after corrections due to the gain of the substitution antenna and the cable loss between the signal generator and the substitution antenna. Repeated the test in extreme test conditions.
Test mode:	Refer to section 5.2 for details
Test Instruments:	Refer to section 6.0 for details

Measurement Data: The detailed test data see Appendix for SRD 5.8G

7.3.2 Frequency Range

Test Requirement:	ETSI EN 300 440 clause 4.2.3
Test Method:	ETSI EN 300 440 clause 4.2.3.3
Limit:	Within the band 5.725-5.875GHz
Test procedure:	Radiated measurements shall be performed in an anechoic chamber. 1 The transmitter under test shall be placed on the support in its standard position and switched on. 2 The test antenna shall be oriented initially for vertical polarization. The test antenna shall be raised or lowered, through the specified height range until the maximum signal level is detected on the measuring receiver. 3 The transmitter shall be rotated through 360° about a vertical axis to maximize the received signal. 4 The test antenna shall be raised or lowered again, if necessary, through the specified height range until a maximum is obtained. This level shall be recorded. 5 This measurement shall be repeated for horizontal polarization. 6 The substitution antenna, shall replace the transmitter antenna in the same position and in vertical polarization. The frequency of the signal generator shall be adjusted to the transmitter (carrier) frequency. 7 Steps 2> to 5> shall be repeated. 8 The input signal to the substitution antenna shall be adjusted in level until an equal or a known related level to that detected from the transmitter is obtained in the test receiver. 9 This measurement shall be repeated with horizontal polarization. 10 The radiated power is equal to the power supplied by the signal generator, increased by the known relationship if necessary and after corrections due to the gain of the substitution antenna and the cable loss between the signal generator and the substitution antenna. 11 Repeated the test in extreme test conditions. 12 The measurement procedure shall be as follows: 12.1 Put the spectrum analyser in video averaging mode with a minimum of 50 sweeps selected; 12.2 Select the lowest operating frequency of the equipment under test and activate the transmitter with modulation applied. The RF emission of the equipment shall be displayed on the spectrum analyser; 12.3 Using the marker of the spectrum analyser, find the lowest frequency below the operating frequency at which the spectral power density drops below the level of -30dBm/30KHz, This frequency shall be recorded in the test report; 12.4 Select the highest operating frequency of the equipment under test and find the highest frequency at which the spectral power density drops below the level of -30dBm/30KHz. This frequency shall be recorded in the test report; The difference between the frequencies measured in steps 12.3> and 12.4> is the operating frequency range. It shall be recorded in the



	test report.
Test mode:	Refer to section 5.2 for details
Test Instruments:	Refer to section 6.0 for details

Measurement Data: The detailed test data see Appendix for SRD 5.8G

7.3.3 Duty Cycle

The EUT is general use, duty cycle doesn't require.

7.3.4 Transmitter Spurious emissions

Test Requirement:	ETSI EN 300 440 clause 4.2.4								
Test Method:	ETSI EN 300 440 clause 4.2.4.3								
Receiver setup:	Frequency $\leq$ 1000MHz; RBW=100KHz, VBW=300KHz, Detector=Quasi-Peak Frequency $>$ 1000MHz; RBW=1MHz, VBW=3MHz, Detector=peak								
Limit:	<table> <tr> <th>Frequency</th><th>Limit (dBm)</th></tr> <tr> <td>47 MHz to 74 MHz 87.5 MHz to 108 MHz 174 MHz to 230 MHz 470 MHz to 862 MHz</td><td>-54</td></tr> <tr> <td>Other frequencies $\leq$ 1 000 MHz</td><td>-36</td></tr> <tr> <td>Frequencies $>$ 1 000 MHz</td><td>-30</td></tr> </table>	Frequency	Limit (dBm)	47 MHz to 74 MHz 87.5 MHz to 108 MHz 174 MHz to 230 MHz 470 MHz to 862 MHz	-54	Other frequencies $\leq$ 1 000 MHz	-36	Frequencies $>$ 1 000 MHz	-30
Frequency	Limit (dBm)								
47 MHz to 74 MHz 87.5 MHz to 108 MHz 174 MHz to 230 MHz 470 MHz to 862 MHz	-54								
Other frequencies $\leq$ 1 000 MHz	-36								
Frequencies $>$ 1 000 MHz	-30								
Test Frequency range:	25MHz to 25GHz								
Test setup:	Below 1GHz  Above 1GHz 								
Test procedure:	Substitution method was performed to determine the actual ERP emission levels of the EUT. The following test procedure as below: ■ Below 1GHz test procedure: 1 On the test site as test setup graph above, the EUT shall be placed at the 1.5m support on the turntable and in the position closest to normal use as declared by the provider. 2 The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter. The output of the test antenna shall be connected to the measuring receiver.								

	3 The transmitter shall be switched on, if possible, without modulation and the measuring receiver shall be tuned to the frequency of the transmitter under test. 4 The test antenna shall be raised and lowered from 1m to 4m until a maximum signal level is detected by the measuring receiver. Then the turntable should be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver. 5 Repeat step 4 for test frequency with the test antenna polarized horizontally. 6 Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At the lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground. 7 Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a nonradiating cable. With the antennas at both ends vertically polarized, and with the signal generator tuned to a particular test frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output. 8 Repeat step 7 with both antennas horizontally polarized for each test frequency. 9 Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps 7 and 8 by the power loss in the cable between the generator and the antenna, and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna by the following formula: $ERP(dBm) = Pg(dBm) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$ where: Pg is the generator output power into the substitution antenna. ■ Above 1GHz test procedure: Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber, and the test antenna do not need to raise from 1 to 4m, just test in 1.5m height.
Test mode:	Refer to section 5.2 for details
Test Instruments:	Refer to section 6.0 for details

Measurement Data: The detailed test data see Appendix for SRD 5.8G

7.3.5 Additional Requirement for FHSS Equipment

7.3.6 Hopping Channel Number

Test Requirement:	ETSI EN 300 440 clause 4.2.6
Test Method:	ETSI EN 300 440 clause 4.2.6
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	≥20 channels
Test results:	N/A: The EUT not a FHSS equipment

7.3.7 Dwell time

Test Requirement:	ETSI EN 300 440 Clause 4.2.6
Test Method:	ETSI EN 300 440 Clause 4.2.6
Limit:	FHSS modulation shall make use of at least 20 channels hopping over >90 % of the assigned frequency band. The dwell time per channel shall not exceed 1 s. While the equipment is operating (transmitting and/or receiving) each channel of the hopping sequence shall be occupied at least once during a period not exceeding four times the product of the dwell time per hop and the number of channels.
Result:	N/A: The EUT not a FHSS equipment

7.4 Receiver Requirements


7.4.1 Receiver Classification

Table 5 of ETSI EN 300 440

Receiver category	Relevant receiver clauses	Risk assessment of receiver performance
1	4.3.3, 4.3.4 and 4.3.5	Highly reliable SRD communication media; e.g. serving human life inherent systems (may result in a physical risk to a person).
2	4.3.4 and 4.3.5	Medium reliable SRD communication media e.g. causing inconvenience to persons, which cannot simply be overcome by other means.
3	4.3.5	Standard reliable SRD communication media e.g. Inconvenience to persons, which can simply be overcome by other means (e.g. manual).


Remark: the EUT belong to Category 3.

7.4.2 Adjacent Channel Selectivity

Test Requirement:	ETSI EN 300 440 Clause 4.3.3								
Test Method:	ETSI EN 300 440 Clause 4.3.3.3								
Limit:	Table 6: Limit for adjacent channel selectivity <table> <tr> <th>Receiver category</th><th>Limit</th></tr> <tr> <td>1</td><td>-30 dBm + k</td></tr> <tr> <td>2</td><td>No limit</td></tr> <tr> <td>3</td><td>No limit</td></tr> </table>	Receiver category	Limit	1	-30 dBm + k	2	No limit	3	No limit
Receiver category	Limit								
1	-30 dBm + k								
2	No limit								
3	No limit								
Test setup:	 <pre> graph LR A[Signal generator A] --- C[Combining network] B[Signal generator B] --- C C --- D[DUT] </pre>								
Test procedure:	Signal generator A shall be at the nominal frequency of the receiver, with normal modulation of the wanted signal. Signal generator B shall be unmodulated and shall be adjusted to the adjacent channel centre frequency immediately above that of the wanted signal. Initially signal generator B shall be switched off and using signal generator A the level that still gives sufficient response shall be established. The output level of generator A shall then be increased by 3 dB. Signal generator B is then switched on and adjusted until the wanted criteria are met. This level shall be recorded. The measurements shall be repeated with signal generator B unmodulated and adjusted to the adjacent channel centre immediately below the wanted signal. The adjacent channel selectivity shall be recorded for the upper and lower adjacent channels as the level in dBm of the unwanted signal.								
Test mode:	Refer to section 5.2 for details								
Test Instruments:	Refer to section 6.0 for details								



Measurement Data: The detailed test data see Appendix for SRD 5.8G

7.4.3 Blocking or desensitization

Test Requirement:	ETSI EN 300 440 clause 4.3.4								
Test Method:	ETSI EN 300 440 clause 4.3.4.3								
Limit:	Table 7: Limits for blocking or desensitization <table> <tr> <th>Receiver category</th><th>Limit</th></tr> <tr> <td>1</td><td>-30 dBm + k</td></tr> <tr> <td>2</td><td>-45 dBm + k</td></tr> <tr> <td>3</td><td>No limit</td></tr> </table>	Receiver category	Limit	1	-30 dBm + k	2	-45 dBm + k	3	No limit
Receiver category	Limit								
1	-30 dBm + k								
2	-45 dBm + k								
3	No limit								
Test setup:	 <pre> graph LR SGA[Signal Generator A] --- C[Combiner] SGB[Signal Generator B] --- C C --- EUT[EUT] </pre>								
Test procedure:	Two signal generators A and B shall be connected to the receiver via a combining network to the receiver, either: - via a test fixture or a test antenna to the receiver integrated, dedicated or test antenna; or - directly to the receiver permanent or temporary antenna connector. The method of coupling to the receiver shall be stated in the test report. Signal generator A shall be at the nominal frequency of the receiver, with normal modulation of the wanted signal. Signal generator B shall be unmodulated and shall be adjusted to a test frequency at approximately 10 times, 20 times and 50 times of the receive channel bandwidth above upper band edge of the receive channel. Initially signal generator B shall be switched off and using signal generator A the level which still gives sufficient response shall be established. The output level of generator A shall then be increased by 3 dB. Signal generator B is then switched on and adjusted until the wanted criteria are met. This level shall be recorded. The measurement shall be repeated with the test frequency for signal generator B at approximately 10 times, 20 times and 50 times of the receive channel bandwidth below the lower band edge of the receive channel. The blocking or desensitization shall be recorded as the level in dBm of lowest level of the unwanted signal (generator B). For tagging systems (e.g. RF identification, anti-theft, access control, location and similar systems) signal generator A may be replaced by a physical tag positioned at 70 % of the measured system range in metres. In this case, the blocking or desensitization shall be recorded as the ratio in dB of lowest level of the unwanted signal (generator B) resulting in a non-read of the tag. to the declared sensitivity of the receiver +3 dB.								
Test Instruments:	Refer to section 6.0 for details								
Test mode:	Refer to section 5.2 for details								

Measurement Data: The detailed test data see Appendix for SRD 5.8G

7.4.4 Spurious emissions

Test Requirement:	ETSI EN 300 440 clause 4.3.5		
Test Method:	ETSI EN 300 440 clause 4.3.5.3		
Receiver setup:	Frequency≤1000MHz;RBW=100KHz,VBW=300KHz,Detector=Quasi-Peak Frequency>1000MHz; RBW=1000KHz, VBW=3000KHz, Detector= Peak		
Limit:	Frequency	Limit(narrowband)	Limit(wideband)
	25MHz to 1000 MHz	2nW(-57dBm)	-107dBm/Hz
	1GHz to 25GHz	20nW(-47dBm)	-97dBm/Hz
Test Frequency range:	25MHz to 25GHz		
Test setup:	Below 1GHz  Above 1GHz 		
Test procedure:	Substitution method was performed to determine the actual ERP emission levels of the EUT. The following test procedure as below: 1>.Below 1GHz test procedure: 1. On the test site as test setup graph above, the EUT shall be placed at the 1.5m support on the turntable and in the position closest to normal use as declared by the provider. 2. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to the frequency of the transmitter.The output of the test antenna shall be connected to the measuring receiver. 3. The transmitter shall be switched on, if possible, without modulation and the measuring receiver shall be tuned to the frequency of the transmitter under test. 4. The test antenna shall be raised and lowered from 1m to 4m until a maximum signal level is detected by the measuring receiver. Then the		

	turntable should be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver. 5. Repeat step 4 for test frequency with the test antenna polarized horizontally. 6. Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At the lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground. 7. Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a nonradiating cable. With the antennas at both ends vertically polarized, and with the signal generator tuned to a particular test frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output. 8. Repeat step 7 with both antennas horizontally polarized for each test frequency. 9. Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps 7 and 8 by the power loss in the cable between the generator and the antenna, and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna by the following formula: $ERP(dBm) = Pg(dBm) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$ where: Pg is the generator output power into the substitution antenna. 2>.Above 1GHz test procedure: Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber, and the test antenna do not need to raise from 1 to 4m, just test in 1.5m height.
Test mode:	Refer to section 5.2 for details
Test Instruments:	Refer to section 6.0 for details

Measurement Data: The detailed test data see Appendix for SRD 5.8G

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----