

RF Exposure Evaluation Limits

KDB447498 D01 General RF Exposure Guidance v06

1.1. Evaluation method

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition(s), listed below, is (are) satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The minimum test separation distance defined in 4.1 f) is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander. To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified, typically in the SAR measurement or SAR analysis report, by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting are required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops and tablets, etc..

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]$$

- $[\sqrt{f \text{ (GHz)}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

1.2. Evaluation Results

Worst-Case mode Conducted Output Power Results

Band	Mode	Frequency (MHz)	Maximum Output Power (dBm)	Max Tune up power (dBm)	Max Tune up power (mW)
2.4G SRD	GFSK	2404	8.32	8.5	7.08
BLE	GFSK	2480	2.27	2.5	1.78
BT	GFSK	2480	2.29	2.5	1.78
2.4G WIFI	DSSS	2437	9.25	9.5	8.91
5.8G WIFI	OFDM	5795	11.56	11.6	14.45

Calculation results: Worst-Case mode

Band	Max Tune up power (dBm)	Result	SAR Test Exclusion Threshold	SAR Test Exclusion
2.4G SRD	8.5	2.22	< 7.5	Yes
BLE	2.5	0.56	< 7.5	Yes
BT	2.5	0.56	< 7.5	Yes
2.4G WIFI	9.5	2.79	< 7.5	Yes
5.8G WIFI	12.0	6.96	< 7.5	Yes

Note: device is a Professional model airplane remote control, handheld use.

1.3. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06 section 4.3.1.

**** END OF REPORT ****